



เยี่ยมในความเย็นและคุณภาพ

Packaged Air Cooled Chiller

Model OAC



Specification

R410a
Refrigerant

MODEL OAC		36	36	48	60	80	100	120	150	200
CAPACITY	KW	10.3	10.3	14.0	17.9	23.5	31.4	36.0	46.0	61.5
	BTU/HR	35300	35300	47900	61000	80100	107000	123000	157000	213000
WATER FLOW RATE	GPM	7.06	7.06	9.58	12.2	16.02	21.4	24.6	31.4	42.6
CAPACITY STEP	%	0-100								
POWER SUPPLY	V	220-1-50		380-3-50						
CURRENT TOTAL	AMP.	19.35	8.23	11.725	14.45	17.7	24.14	26.95	35.28	39.7
COMPRESSOR	TYPE	SCROLL TYPE								
EVAPORATOR	TYPE	DIRECT EXPANSION SHELL AND TUBES								
CONDENSER	TYPE	CROSS FIN COIL (WAFFLE LOUVER FIN)								
FAN	FACE AREA	FT2	8.05	8.05	8.05	13.05	13.05	17.8	17.8	35.65
	NO.x ROW		2	2	2	2	3	2	3	2
	TYPE		PROPELLER							
	NO.		1	1	1	2	2	2	2	2
	FAN DAI.	INC	20	20	20	20	20	20	24	28
	MOTOR INPUT	HP	1/6	1/6	1/6	1/6	1/6	1/6	1/2	3/4
REFRIGERANT	TYPE	R 410								
CONNECTION	WATER IN/OUT	INC	1	1	1	2	2	2	2	2
DIMENSION	HIGHT	MM.	1276.5	1276.5	1276.5	1276.5	1368.5	1368.5	2107	2107
	WIDTH	MM.	1098	1098	1098	1555	1555	1720	2292	2292
	DEPTH	MM.	767	767	767	767	767	767	1005	1005
APPROX WEIGHT	KG	280	280	310	340	410	460	480	650	750

MODEL OAC			200-2	250	250-2	300-2	400-2	400-4	500-2	500-4	600-4
CAPACITY	KW		62.4	72.1	72.1	92.0	120.0	119.9	146.5	146.5	181.7
	BTU/HR		213000	246000	246000	314000	409500	409000	500000	500000	620000
WATER FLOW RATE	GPM		42.6	49.2	49.2	62.8	81.9	81.8	100	100	124
CAPACITY STEP	%		0-50-100	0-100	0-50-100			0-25-50-75-100	0-50-100	0-25-50-75-100	
POWER SUPPLY	V		380-3-50								
CURRENT TOTAL	AMP.		47.08	49.2	52.7	70.55	79.4	94.15	98.4	105.4	141.1
COMPRESSOR	TYPE		SCROLL TYPE								
EVAPORATOR	TYPE		DRIECT EXPANSION SHELL AND TUBES								
CONDENSER	TYPE		CROSS FIN COIL (WAFFLE LOUVER FIN)								
FAN	FACE AREA	FT2	35.65	35.65	35.65	55.48	71.3	71.3	71.3	71.3	110.9
	NO.xROW		2	3	3	2	2	2	3	3	2
	TYPE		PROPELLER								
	NO.		2	2	2	3	4	4	4	4	6
	FAN DAI.	INC	28	28	28	28	28	28	28	28	28
	MOTOR INPUT	HP	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4
REFRIGERANT	TYPE		R 410								
CONNECTION	WATER IN/OUT	INC	2	2	2	2-1/2	2-1/2	2-1/2	3	3	3
DIMENSION	HIGHT	MM.	2107	2107	2107	2107	2107	2107	2107	2107	2124
	WIDTH	MM.	2292	2292	2292	3431	2292	2292	2292	2292	3442
	DEPTH	MM.	1005	1005	1005	1005	2009	2009	2009	2009	2009
APPORX WEIGHT		KG	825	820	920	975	1100	1100	1475	1475	1580

Note: Rating BTU/Hr. 45 °F evaporating temp. Rating BTU/Hr. 95 °F ambient air for outdoor unit. Specification subject to change without notice

เครื่องปรับอากาศคุณภาพสูง ผลิตภัณฑ์จากโรงงานที่ได้รับการรับรองมาตรฐาน ISO9001:2015, ISO14001:2015, TIS18001:2011, ISO45001:2018, ISO/IEC17025:2005

