

AIR-COOLED CONDENSING UNIT



Model OAB 80 - OAB 150



Model OAB 200
Model OAB 200-2 - OAB 400-2
Model OAB 400-4



Model OAB 500-2
Model OAB 500-4 - OAB 600-4

CONDENSING SPECIFICATION (OUTDOOR UNIT)

MODEL		OAB 80	OAB 100	OAB 125	OAB 150	OAB 200	OAB 200-2	OAB 250	OAB 250-2	
COOLING CAPACITY	BTU/Hr.	78,000	107,000	123,000	157,000	213,000	213,000	246,000	246,000	
POWER SUPPLY	V / Ph / Hz	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	
COMPRESSOR	TYPE	SCROLL								
REFRIGERANT	TYPE	R410a	R410a	R410a	R410a	R410a	R410a	R410a	R410a	
FAN MOTOR	TYPE	PROPELLER FAN								
FAN DIAMETER	INCH	24	24	28	30	24	24	28	28	
CONNECTION	SUCTION	INCH	7/8	1-1/8	1-3/8	1-3/8	1-5/8	1-3/8 x 2	1-5/8	1-3/8 x 2
	LIQUID	INCH	1/2	5/8	5/8	5/8	5/8	5/8 x 2	7/8	5/8 x 2
DIMENSION	WIDTH	CM	96.5	96.5	140	140	193	193	283	283
	HEIGHT	CM	90.3	105	93.7	103.9	105	105	101	101
	DEPTH	CM	75	75	112.5	112.5	75.5	75.5	112.5	112.5
APPROX. WEIGHT	KG.	150	170	200	240	380	350	400	400	

MODEL		OAB 300-2	OAB 400-2	OAB 400-4	OAB 500-2	OAB 500-4	OAB 600-3	OAB 600-4	
COOLING CAPACITY	BTU/Hr.	314,000	420,000	420,000	500,000	500,000	620,000	620,000	
POWER SUPPLY	V / Ph / Hz	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	
COMPRESSOR	TYPE	SCROLL							
REFRIGERANT	TYPE	R410a	R410a	R410a	R410a	R410a	R410a	R410a	
FAN MOTOR	TYPE	PROPELLER FAN							
FAN DIAMETER	INCH	30	30	30	30	30	30	30	
CONNECTION	SUCTION	INCH	1-5/8 x 2	1-5/8 x 2	1-1/8 x 4	1-5/8 x 2	1-3/8 x 4	1-5/8 x 3	1-3/8 x 4
	LIQUID	INCH	5/8 x 2	5/8 x 2	5/8 x 4	7/8 x 2	5/8 x 4	5/8 x 3	5/8 x 4
DIMENSION	WIDTH	CM	283	283	283	333	333	333	333
	HEIGHT	CM	111.5	143.7	143.7	118.5	118.5	118.5	118.5
	DEPTH	CM	112.5	112.5	112.5	161.6	161.6	161.6	161.6
APPROX. WEIGHT	KG.	480	600	600	750	750	800	800	

เครื่องปรับอากาศคุณภาพสูง ผลิตจากโรงงานที่ได้รับการรับรองมาตรฐาน ISO9001:2015, ISO14001:2015, TIS18001:2011, ISO45001:2018, ISO/IEC17025:2005

